


DUNLOP DIY ADHESIVE SELECTOR GUIDE

	Walls	Floors	Indoors	Outdoors	Over Dunlop Undertile Waterproofing Membrane	Constantly Immersed e.g. swimming pools	Concrete/sand-cement screeds	Fibre-cement sheets	Plasterboard	Painted Surfaces (oil-based, adequately prepared)	Existing Tiles - no grinding glaze	Existing Tiles - remove the glaze	Timber Indoor (particleboard only)	Vinyl Tiles (roughened)	Metal	Fibreglass
Wall Tile Adhesive	●		●				●	●	●	●						
Floor Tile Adhesive		●	●	●			●	●				●				
Wall & Floor Tile Adhesive	●	●	●	●	●		●	●	●	●		●	● ³	●	●	
Premixed Resaflex	●	● ¹	●				●	●	●	●						
Tile-All	●	●	●	●	●	●	●	●	●	●	● ⁵		●	●	●	● ⁴
Tile-All <i>Plus</i>	●	●	●	●	●	● ⁶	●	●	●	●	●		●		●	●
Wallfix Tile Adhesive	●		●				●	●	●	●						
Floorfix Tile Adhesive		●	●	● ²			●									
Trade Resaflex	●	●	●	●			●	●	●			●				

¹ Premixed Resaflex can only be used on floors when tiling over fibre-cement sheet

² Covered outdoor only (where movement is anticipated use with Dunlop Primer & Additive)

³ Prior to tiling, a skim coat of Dunlop Tile-All must be applied to the substrate first. Refer to product datasheet on website.

⁴ The surface must be roughened prior to tiling as per instructions on packaging.

⁵ Grinding the glaze is required in external applications.

⁶ Minor repairs only.

Please refer to pages 8-10 for DUNLOP TRADE RANGE adhesive applications.

We recommend priming all porous substrates (particularly fibre cement sheets, cement renders) with Dunlop Primer & Additive prior to tiling