



TIMBER FLOOR ADHESIVE

DUNLOP®TIMBER FLOOR ADHESIVE is a water based, flexible adhesive for the installation of most types of mosaic and block parquet to most common concrete and timber surfaces.

SURFACE PREPARATION

Surfaces must be dry, smooth, clean and free of any contaminants that may limit adhesion to the subfloor.

Highly porous concrete or timber subfloors should be primed with DUNLOP®TIMBER FLOOR ADHESIVE broken down with water at a ratio of 5 parts water to 1 part adhesive. Wait for the primed surface to dry.

Imperfections in the subfloor can be fixed using either DUNLOP®FLOOR LEVELLER or DUNLOP®FLOOR REPAIRERS. Refer to respective products for suitable substrate information and application instructions.

The adhesive should not be used in extremely hot or cold conditions (i.e. below 10°C or above 35°C). New concrete surfaces must be completely cured.

APPLICATION

- 1 Spread adhesive evenly using a "V" notched trowel, which is 3mm from point to point and 5mm deep. Work with the trowel in upright position, and notched edge pressed down hard against the floor.
- 2 Laying the timber floor (about 2 square metres at a time) should be started immediately after spreading the adhesive. On smooth concrete floors, or under cold or humid conditions, as much as 30 minutes may be available for laying. In hot or dry conditions, this time may be reduced.

Sanding and polishing can commence 10 days after completion of timber flooring installation.

COVERAGE

4L of DUNLOP®TIMBER FLOOR ADHESIVE will cover approximately 3-4m². Coverage will vary depending on the condition of the subfloor and application technique.

CLEAN UP

Clean tools and equipment immediately after use, with warm soapy water. Dried adhesive can be removed with mineral turps.

SHELF LIFE

12 months when stored in the original unopened container at 20°C.

CAUTION

Always ensure there is adequate ventilation when using DUNLOP®TIMBER FLOOR ADHESIVE.

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturer's instructions.

TECHNICAL DATA

Characteristic of Product:

Colour: Yellow/brown

Characteristic of Mix

Mixing: Premixed

Mix S.G: 1.6kg/L

Application Properties (at 23°C and 50% relative humidity)

Drying time: 15-30 minutes

Application temperature: 10-35°C

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

Made under license

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005
20 Powers Road, Seven Hills NSW 2147 Australia.
Ph: +61 2 9851 9199 Fax: +61 2 9674 5621

SALES OFFICES:

Sydney: Ph+61 2 9851 9100 Fax+61 2 9838 7970
Brisbane: Ph+61 7 3881 3888 Fax+61 7 3881 3188
Melbourne: Ph+61 3 9308 9255 Fax +61 3 9308 9332
Adelaide: Ph+61 8 8268 2511 Fax+61 8 8345 3207
Perth: Ph+61 8 9455 1644 Fax+61 8 9455 1227
Christchurch: Ph+64 3 384 3029 Fax+64 3 384 9779

Jan06_v1