



FLOOR REPAIRER - Minor Imperfections

DUNLOP® FLOOR REPAIRER - MINOR IMPERFECTIONS is a cement based compound, designed for repairing cracks and imperfections less than 3mm deep and smoothing surfaces before applying floor coverings such as vinyl, carpet and ceramic tile. It can be applied to most surfaces including concrete, fibre-cement sheeting, cement screeds and existing tiles.

SURFACE PREPARATION

Surfaces must be firmly fixed. Clean off dust, oil, grease and all loose contaminating materials or coatings. Ensure surfaces are dry, with no residue or permanent dampness.

MIXING

The mixed material is usable for approximately 15 minutes, depending on temperature and humidity.

1. Use approximately 750ml of water with 1.5kg of the powder.
2. Add powder to clean water in a container and mix to a creamy consistency using a mechanical stirrer or spatula.

APPLICATION

1. Apply the mixed material to the prepared surface using a steel trowel using sufficient pressure to work the material into the surface and to fill all defects.
2. It is not necessary to leave a minimum thickness, use the least amount possible to obtain the required smoothness.
3. Material can be applied to a maximum thickness of 3mm. For thicker areas use DUNLOP® FLOOR REPAIRER FOR CRACKS AND HOLES.
4. Do not rework material after 15 mins.

COVERAGE

Approximately 3m² when applied at 1mm thickness and up to 10m² when applied as a "skim" coat.

DRYING TIME

Material will be dry after 15 minutes, with foot traffic and installation of floor coverings possible after 1 hour.

SHELF LIFE

A shelf life of 12 months is expected when stored in a dry place in original unopened packaging.

PACKAGING

1.5kg

CAUTION

Do not use in continuous immersed conditions or areas subject to water ponding. Keep out of reach of children. Use gloves to prevent skin irritation. Avoid inhaling dust by using a dust mask.

Wash immediately with water if material enters eyes.

MSDS available on request.

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturers instructions. Manufactured under a quality system certified as complying with ISO 9001 by an accredited certification body. Material Safety Data Sheets are available upon request.

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

DUNLOP is a trademark of Ansell Limited and is used under license by ARDEX in Australia and New Zealand.

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005
20 Powers Road, Seven Hills NSW 2147

SALES OFFICES: Brisbane, Sydney, Melbourne, Adelaide, Perth, Christchurch, Auckland and Wellington.

FRMI-05/05_v2